



* Hanover® requires the first two rows of pavers to be strapped together when using Hanover® EdgeFinder™. Hanover® recommends the use of a 3" wide, 22 gauge flat stainless steel strap at a length of 41 1/8". It is to be anchored to the underside of the pavers using a Zamac Nailin 1/4" x 1 1/4", all metal, provided by Powers Rawl part #2814. See drawing.

* Each project and site conditions are unique. An architect, landscape architect, and/or structural engineer should be consulted to develop a specification suited for the specific project. Neither this drawing nor any of the individual product drawings from Hanover® Architectural Products is intended to be a project specific design. The installation suggestion given in this drawing is only an illustration and not intended to be project specific. Each application and specification for installation should have the attention of an architect, landscape architect and/or structural engineer. As product use and site conditions are not within our control, Hanover® does not guarantee results from use of such products or other information herein: no warranty, express or implied is given.

HANOVER®
Architectural Products

5000 Hanover Road
Hanover, PA 17331
800.426.4242
info@hanoverpavers.com
www.hanoverpavers.com

DESIGNED		SCALE: 6"=1'
DETAILED	J.L.F.	DATE: 11/5/18
TRACED		PCS:--
CHECKED		DWG. NO:1 of 1
APPROVED		LOCATION: HANOVER
		PRODUCT: HANOVER® EDGEFINDER™
*LENGTH AND WIDTH DIMENSIONS ARE MADE WITH A TOLERANCE OF +/- 1/8"		
THICKNESS AND HEIGHT DIMENSIONS ARE MADE WITH A TOLERANCE OF +/- 1/8"		
*DIMENSIONS SHOWN ARE NOMINAL. PRODUCTS ARE MADE TO FIT METRIC MODULES.		

HANOVER® EDGEFINDER™
Installation Guideline -
Strapping Option